

NM-HDV2-1T1/E1 - Cisco High-Density Digital Voice/Fax Network Modules

Model: NM-HDV2-1T1/E1 | Brand: CISCO

Product Overview

IP Communications High-Density Digital Voice NM with 1 T1/E1 Cisco Router Network Module

Product page: <https://www.linknewnet.com/products/nm-hdv2-1t1-e1>

Quick Specifications

Attribute	Value
Model	NM-HDV2-1T1/E1
Module Type	Network Module
Voice Ports	1 T1/E1
Interface	T1/E1
High-Density Digital Voice	Yes
Supported Platforms	Cisco Routers
Voice Connectivity	IP Communications
Dimensions	13.3 cm x 29.0 cm x 3.0 cm (5.25 in x 11.5 in x 1.2 in)
Maximum Power Consumption	38.4 watts
Operating Temperature	0 to 40°C (32 to 104°F)
Storage Temperature	-40 to 80°C (-40 to 176°F)
Relative Humidity	5% to 95% (non-condensing)
Compliance Standards	FCC, CE, UL
MTBF	400,000 hours
Redundancy	Yes
RoHS Compliant	Yes
Hot-Swappable	Yes
Product Code	NM-HDV2-1T1/E1
Brand	CISCO

Replacement / Alternative Options

If the NM-HDV2-1T1/E1 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
NM-HDV2	IP Communications High-Density Digital Voice Network Module Cisco Router Network Module
NM-HDV2-2T1/E1	IP Communications High-Density Digital Voice NM with 2 T1/E1 Cisco Router Network Module

Request availability: [Ask for current stock](#) of NM-HDV2-1T1/E1 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).