

Cisco Aironet Power Injector AIR-PWRINJ5

Model: ON-PWRINJ5 | Brand: CISCO

Product Overview

Aironet power injector AIR-PWRINJ5, 802.3af, 15.4W

Product page: <https://www.linknewnet.com/products/on-pwrinj5>

Quick Specifications

Attribute	Value
Model	AIR-PWRINJ5
Brand	Cisco
Power Supply	802.3af
Power Output	15.4W
Input Voltage Range	100-240VAC
Input Frequency Range	50-60Hz
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	10% to 85% non-condensing
Storage Temperature	-30°C to 70°C (-22°F to 158°F)
Storage Humidity	5% to 90% non-condensing
Certifications	FCC, CE, RCM, IC
LED Status Indicators	Power, Link
Security Features	Overload protection, Short circuit protection
Mounting Option	Wall mount
Connectors	2 RJ-45 10/100/1000 (Cat 5 or better Ethernet cable)
Dimensions (L, W, H)	165 mm x 65 mm x 36 mm (6.5 in x 2.6 in x 1.4 in)
Stacking restrictions	Do not stack. Do not bundle the power injector and AC power cable.
Product Code	ON-PWRINJ5
Brand	CISCO

Replacement / Alternative Options

If the ON-PWRINJ5 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ON-PWRINJ3	Cisco AP power option AIR-PWRINJ3 Power Injector for 1100, 1130AG, 1200 1230AG, 1240AG, 521
ON-PWRINJ3	Cisco AP power option AIR-PWRINJ3 Power Injector for 1100, 1130AG, 1200 1230AG, 1240AG, 521

Request availability: [Ask for current stock](#) of ON-PWRINJ5 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).