

PA-MC-2T1= - Cisco 7600 Port Adapter

Model: PA-MC-2T1= | Brand: CISCO

Product Overview

Cisco 7600 2 port multichannel T1 port adapter with integrated CSU/DSUs

Product page: <https://www.linknewnet.com/products/pa-mc-2t1>

Quick Specifications

Attribute	Value
Model	PA-MC-2T1=
Product Type	Port Adapter
Compatibility	Cisco 7600 Series Routers
Number of Ports	2
Port Type	Multichannel T1
Integrated CSU/DSUs	Yes
Data Transfer Rate	Up to 1.544 Mbps per T1
Protocol Support	HDLC, PPP, and Frame Relay
Connector Type	RJ-48C
Line Code	AMI/B8ZS
Line Framing	SF/ESF
LED Indicators	Status LEDs for each port
Power Consumption	35 Watts
Operating Temperature	0 to 40°C (32 to 104°F)
Storage Temperature	-20 to 65°C (-4 to 149°F)
Operating Humidity	10% to 90% (non-condensing)
Storage Humidity	5% to 95% (non-condensing)
Dimensions (WxDxH)	8.5 in x 7.2 in x 1.8 in
Product Code	PA-MC-2T1=
Brand	CISCO

Replacement / Alternative Options

If the PA-MC-2T1= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PA-MC-2E1/120	Cisco 7200 Series 2 port multichannel E1 port adapter with G.703 120ohm interf
PA-MC-2E1/120=	Cisco 7600 2 port multichannel E1 port adapter with G.703 120ohm interf

Request availability: [Ask for current stock](#) of PA-MC-2T1= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).