

PA-MC-4T1= - Cisco 7600 Port Adapter

Model: PA-MC-4T1= | Brand: CISCO

Product Overview

Cisco 7600 4 port multichannel T1 port adapter with integrated CSU/DSUs

Product page: <https://www.linknewnet.com/products/pa-mc-4t1>

Quick Specifications

Attribute	Value
Model	PA-MC-4T1= (USED)
Port Type	T1
Number of Ports	4
Channels Supported	Multichannel
Integrated CSU/DSU	Yes
Compatibility	Cisco 7600 Series
Data Rate	1.544 Mbps (per T1 line)
Connector Type	RJ-48C
Redundancy	Supported
Network Protocols	HDLC, PPP, Frame Relay
Power Requirements	Varies based on the router model
Dimensions	1.5 x 16.0 x 7.0 inches
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-40 to 167°F (-40 to 75°C)
Relative Humidity	10% to 90% (non-condensing)
Software Support	Cisco IOS
Regulatory Approvals	FCC Part 15, CE
Warranty	90 days, vendor-specific
Use Case	Enterprise WAN Connectivity
Product Code	PA-MC-4T1=
Brand	CISCO

Replacement / Alternative Options

If the PA-MC-4T1= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PA-MC-2E1/120	Cisco 7200 Series 2 port multichannel E1 port adapter with G.703 120ohm interf
PA-MC-2E1/120=	Cisco 7600 2 port multichannel E1 port adapter with G.703 120ohm interf

Request availability: [Ask for current stock](#) of PA-MC-4T1= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).