

PVDM2-12DM - Cisco Packet Voice Digital Signal Processor Modules

Model: PVDM2-12DM | Brand: CISCO

Product Overview

12 Port Digital Modem Module

Product page: <https://www.linknewnet.com/products/pvdm2-12dm>

Quick Specifications

Attribute	Value
Model	PVDM2-12DM
Type	Digital Modem Module
Number of Ports	12
Port Type	Digital
Compatibility	Cisco ISR G2 Series
Data Rate	Up to 64 Kbps per channel
Protocols Supported	V.90, V.92
Voice Channels	12
Mounting	Internal
Power Consumption	Low Power
Environmental Operating Range	0 to 40°C
Storage Temperature	-40 to 70°C
Humidity	5% to 95% (non-condensing)
Dimensions	Standard
Compliance Standards	CE, FCC, UL
MTBF	Long Life
LED Indicators	Port Status
Support	24/7 Technical Support
Software Compatibility	Cisco IOS
Product Code	PVDM2-12DM
Brand	CISCO

Replacement / Alternative Options

If the PVDM2-12DM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PVDM2-16	16-Channel Packet Voice/Fax DSP Module
PVDM2-24DM	24 Port Digital Modem Module

Request availability: [Ask for current stock](#) of PVDM2-12DM or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).