

PVDM2-24DM - Cisco Packet Voice Digital Signal Processor Modules

Model: PVDM2-24DM | Brand: CISCO

Product Overview

24 Port Digital Modem Module

Product page: <https://www.linknewnet.com/products/pvdm2-24dm>

Quick Specifications

Attribute	Value
Model	PVDM2-24DM
Number of Ports	24
Cisco DSP Technology	PVDM2
Compatibility	Cisco 2800 and 3800 Series Integrated Services Routers
Modem Interface	Digital
Data Rates Supported	V.92 Modem Speeds
Built-in Codecs	G.711, G.729, G.726, iLBC
VoIP Features	Echo Cancellation, Voice Activity Detection, Comfort Noise Generation
Echo Cancellation	128 ms tail length
Configuration and Management	CLI, SNMPv3
Supported Platforms	Cisco IOS Software
Power Consumption	12W
Operating Temperature Range	0°C to 40°C (32°F to 104°F)
Storage Temperature Range	-20°C to 65°C (-4°F to 149°F)
Humidity	10% to 90%, non-condensing
Product Type	Digital Modem Module
Compliance Standards	FCC, CE, UL, CCC
Product Code	PVDM2-24DM
Brand	CISCO

Replacement / Alternative Options

If the PVDM2-24DM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PVDM2-12DM	12 Port Digital Modem Module
PVDM2-16	16-Channel Packet Voice/Fax DSP Module

Request availability: [Ask for current stock](#) of PVDM2-24DM or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).