

PVDM2-36DM - Cisco Packet Voice Digital Signal Processor Modules

Model: PVDM2-36DM | Brand: CISCO

Product Overview

36 Port Digital Modem Module

Product page: <https://www.linknewnet.com/products/pvdm2-36dm>

Quick Specifications

Attribute	Value
Hardware Platform Compatibility	Cisco 2800, 2900, 3800, and 3900 Series
Fax Data Protocols	· ITU-T V.17 · ITU-T V.33 · ITU-T V.29 · ITU-T V.27ter · ITU-T V.21 channel 2 · Group 3 fax class 2 · Fax auto detection
ISDN Support	· HDLC · Link Access Procedure, Balanced (LAPB) · Rate adaptation (V.110) · V.120 incoming · X.75
Weight	2.4 oz (68 g)
Error Correction Link Access Protocols	· ITU-T V.42 Link Access Procedure for Modems (LAPM) · Microcom Network Protocol (MNP) 2-4
Data Compression Protocols	· V.42bis (with 2-KB dictionaries) · V.44 · MNP-5
Environment Specification	European ETSI 300-019
Dimensions	· Width 3.08 in. (6.93 cm) · Height 0.75 in. (1.91 cm) · Depth 4.38 in. (9.86 cm)
Product Code	PVDM2-36DM
Brand	CISCO

Replacement / Alternative Options

If the PVDM2-36DM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PVDM2-12DM	12 Port Digital Modem Module
PVDM2-16	16-Channel Packet Voice/Fax DSP Module

Request availability: [Ask for current stock](#) of PVDM2-36DM or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).