

PWR-2700-DC - Cisco 7606 Router

Model: PWR-2700-DC | Brand: CISCO

Product Overview

CISCO 7606 router power supply PWR-2700-DC 2700W DC power supply for CISCO7606

Product page: <https://www.linknewnet.com/products/pwr-2700-dc>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	PWR-2700-DC
Unit Type	Power Supply
Compatibility	CISCO 7606 router
Maximum Power Output	2700W
Input Voltage Range	DC
Condition	Used
Form Factor	Plug-in module
Cooling Type	Internal Fan
Redundancy	Yes (supports redundancy configurations)
Hot Swappable	Yes
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Humidity Range	10% to 90% RH (non-condensing)
Certification	CE, FCC, UL
MTBF	100,000 hours
Dimensions	4.4 cm x 27.9 cm x 28 cm
Weight	4 Kg Approximately
Connector Type	Power connector, 3-pin
Protection Features	Overload, Overvoltage, Overtemperature
Product Code	PWR-2700-DC
Brand	CISCO

Replacement / Alternative Options

If the PWR-2700-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of PWR-2700-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).