

QSFP-40/100-SRBD= - Cisco QSFP28 Module

Model: QSFP-40/100-SRBD= | Brand: CISCO

Product Overview

Cisco 100G and 40G SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF

Product page: <https://www.linknewnet.com/products/qsfp-40-100-srbd>

Quick Specifications

Attribute	Value
Dimensions	13.5 x 18.4 x 72.4 mm
Nominal Wavelength (nm)	855, 908
Modal Bandwidth (MHz*km)* 1	2000 (OM3) 4700 (OM4)
Core Size (Microns)	50.0 50.0
Cable Distance	70m 100m
Power Consumption (W)	3.5
Pull Tab Color	Gray
Transmit Power (dBm) per lane *2	Max:+4 (100G) +5 (40G) Min:-6 (100G) -4 (40G)
Receive Power (dBm) per lane *2*3	Max:4 (100G) 5 (40G) Min: -7.9 (100G) -6 (40G)
Receive Power (dBm) per lane	855, 908
Commercial temperature	•100G: +10C to +60C •40G: +10C to +70C
Storage temperature	-40 to 85°C (-40 to 185°F)
Safety	•Cable jacket of QSFP copper modules is UL E116441 Compliant •QSFP copper cables are ELV compliant
Product Code	QSFP-40/100-SRBD=
Brand	CISCO

Replacement / Alternative Options

If the QSFP-40/100-SRBD= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
QSFP-40G-BD-RX=	QSFP40G BiDi-Monitor Short-reach Transceiver For Data Broker
QSFP-40G-CSR-S=	40GBASE-CSR QSFP Transceiver Module with LC Connector

Request availability: [Ask for current stock](#) of QSFP-40/100-SRBD= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).