

QSFP-40G-BD-RX= - Cisco QSFP+ Module

Model: QSFP-40G-BD-RX= | Brand: CISCO

Product Overview

QSFP40G BiDi-Monitor Short-reach Transceiver For Data Broker

Product page: <https://www.linknewnet.com/products/qsfp-40g-bd-rx>

Quick Specifications

Attribute	Value
Description	Cisco 40GBASE-SR Bi-Directional QSFP Monitor Module for Duplex MMF
Dimensions	13.5 x 18.4 x 72.4 mm
Core Size (microns)	50.0 50.0 50.0
Modal Bandwidth (MHz-km)	500 (OM2) 2000 (OM3) 4700 (OM4)
Cable Distance	30m 100m 150m
Wavelength (nm)	832 - 918
Commercial temperature	3.5
Cable Type	MMF
Storage temperature	Beige(or Gray with "Rx" mark)
Type	40GBASE-SR-BiDi, Duplex MMF, Monitor
Transmit Power (dBm)	Max:\ Min:\
Receive Power (dBm)	Max:+5.0 per lane Min:-6.0 per lane
Transmit and Receive Wavelength (nm)	832 to 918
Operating temperature	+10 to 70 ° C (50 to 158 ° F)
Safety	•Cable jacket of QSFP copper modules is UL E116441 Compliant •QSFP copper cables are ELV Compliant
Product Code	QSFP-40G-BD-RX=
Brand	CISCO

Replacement / Alternative Options

If the QSFP-40G-BD-RX= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
QSFP-40/100-SRBD=	Cisco 100G and 40G SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF
QSFP-40G-CSR-S=	40GBASE-CSR QSFP Transceiver Module with LC Connector

Request availability: [Ask for current stock](#) of QSFP-40G-BD-RX= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).