

# QSFP-40G-CSR-S= - Cisco QSFP+ Module

Model: QSFP-40G-CSR-S= | Brand: CISCO

## Product Overview

40GBASE-CSR QSFP Transceiver Module with LC Connector

Product page: <https://www.linknewnet.com/products/qsfp-40g-csr-s>

## Quick Specifications

| Attribute                            | Value                                                                                              |
|--------------------------------------|----------------------------------------------------------------------------------------------------|
| Description                          | Cisco 40GBASE-CSR QSFP Module for Duplex MMF                                                       |
| Dimensions                           | 13.5 x 18.4 x 72.4 mm                                                                              |
| Core Size (microns)                  | 50.0                                                                                               |
| Modal Bandwidth (MHz-km)             | 2000 (OM3) 4700 (OM4)                                                                              |
| Wavelength (nm)                      | 850                                                                                                |
| Cable Distance                       | 300m 400m                                                                                          |
| Power Consumption (W)                | 3.5                                                                                                |
| Cable Type                           | MMF                                                                                                |
| Pull Tab Color                       | Orange                                                                                             |
| Type                                 | 40GBASE-CSR, Duplex MMF                                                                            |
| Transmit Power (dBm)                 | Max:+3.0 per lane Min:-7.0 per lane                                                                |
| Receive Power (dBm)                  | Max:+3.0 per lane Min:-9.0 per lane                                                                |
| Transmit and Receive Wavelength (nm) | Four lanes: 850, 880, 910, 940                                                                     |
| Commercial temperature               | 0 to 70 ° C (32 to 158 ° F)                                                                        |
| Storage temperature                  | -40 to 85 ° C (-40 to 185 ° F)                                                                     |
| Safety                               | •Cable jacket of QSFP copper modules is UL E116441 Compliant •QSFP copper cables are ELV Compliant |
| Product Code                         | QSFP-40G-CSR-S=                                                                                    |
| Brand                                | CISCO                                                                                              |

## Replacement / Alternative Options

If the QSFP-40G-CSR-S= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                             | Specification                                                 |
|-----------------------------------|---------------------------------------------------------------|
| <a href="#">QSFP-40/100-SRBD=</a> | Cisco 100G and 40G SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF |
| <a href="#">QSFP-40G-BD-RX=</a>   | QSFP40G BiDi-Monitor Short-reach Transceiver For Data Broker  |

Request availability: [Ask for current stock](#) of QSFP-40G-CSR-S= or its alternatives.

## Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).