

QSFP-40G-LR4= - Cisco QSFP+ Module

Model: QSFP-40G-LR4= | Brand: CISCO

Product Overview

QSFP 40GBASE-LR4 OTN Transceiver, LC, 10KM

Product page: <https://www.linknewnet.com/products/qsfp-40g-lr4>

Quick Specifications

Attribute	Value
Description	Cisco 40GBASE-LR4 QSFP Module for SMF with OTU-3 data-rate support
Dimensions	13.5 x 18.4 x 72.4 mm
Core Size (microns)	G.652
Wavelength (nm)	1310
Cable Distance	10km
Power Consumption (W)	3.5
Cable Type	SMF
Pull Tab Color	Blue
Type	40GBASE-LR4 with OTU3 data rate support, 1310 nm, SMF
Transmit Power (dBm)	Max:+2.3 per lane Min:-7.0 per lane
Receive Power (dBm)	Max:+2.3 per lane Min:-13.7 per lane
Transmit and Receive Wavelength (nm)	Four lanes: 1271, 1291, 1311, 1331
Commercial temperature	0 to 70 ° C (32 to 158 ° F)
S torage temperature	-40 to 85 ° C (-40 to 185 ° F)
Safety	•Cable jacket of QSFP copper modules is UL E116441 Compliant •QSFP copper cables are ELV Compliant
Product Code	QSFP-40G-LR4=
Brand	CISCO

Replacement / Alternative Options

If the QSFP-40G-LR4= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
QSFP-40/100-SRBD=	Cisco 100G and 40G SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF
QSFP-40G-BD-RX=	QSFP40G BiDi-Monitor Short-reach Transceiver For Data Broker

Request availability: [Ask for current stock](#) of QSFP-40G-LR4= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).