

QSFP-40G-SR4-S= - Cisco QSFP+ Module

Model: QSFP-40G-SR4-S= | Brand: CISCO

Product Overview

40GBASE-SR4 (IEEE 802.3ba Spec.) QSFP+ transceiver module for MMF, MPO/MTP connector

Product page: <https://www.linknewnet.com/products/qsfp-40g-sr4-s>

Quick Specifications

Attribute	Value
Dimensions	13.5 x 18.4 x 72.4 mm
Pull Tab Color	Beige
Power Consumption (W)	1.5
Cable Type	MMF
Core Size (microns)	50.0 50.0
Modal Bandwidth (MHz-km)	2000 (OM3) 4700 (OM4)
Cable Distance	100m 150m
Type	40GBASE-SR4, 4 lanes, 850 nm MMF
Transmit Power (dBm)	Max:+2,4 per lane Min:-7.6 per lane
Receive Power (dBm)	Max:-2.4 per lane Min:-9.5 per lane
Transmit and Receive Wavelength (nm)	840 to 860
Commercial temperature	0 to 70°C (32 to 158°F)
Storage temperature	-40 to 85°C (-40 to 185°F)
Safety	•Cable jacket of QSFP copper modules is UL E116441 Compliant •QSFP copper cables are ELV Compliant
Product Code	QSFP-40G-SR4-S=
Brand	CISCO

Replacement / Alternative Options

If the QSFP-40G-SR4-S= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
QSFP-40/100-SRBD=	Cisco 100G and 40G SR-BiDi QSFP Transceiver, LC, 100m OM4 MMF
QSFP-40G-BD-RX=	QSFP40G BiDi-Monitor Short-reach Transceiver For Data Broker

Request availability: [Ask for current stock](#) of QSFP-40G-SR4-S= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).