

Huawei S2300 Series Switch S2350-28TP-PWR-EI-AC

Model: S2350-28TP-PWR-EI-AC | Brand: HUAWEI

Product Overview

S2350-28TP-PWR-EI-AC(24 Ethernet 10/100 PoE+ ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC 110/220V)

Product page: <https://www.linknewnet.com/products/s2350-28tp-pwr-ei-ac>

Quick Specifications

Attribute	Value
Item	Description
Memory (RAM)	256 MB
Flash	200 MB
Mean time between failures (MTBF)	78.29 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±6 kV
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Dimensions (W x D x H)	442.0 mm x 310.0 mm x 43.6 mm (17.4 in. x 12.2 in. x 1.72 in.)
Weight	≤ 5 kg (11.02 lb)
Stack ports	Two uplink 1000Base-X optical ports
RPS	Not supported
PoE	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Operating altitude	0-5000 m (0-16404 ft.)
Certification	·EMC certification ·Safety certification ·Manufacturing certification
Ethernet	MAC:16K VLAN:4K Maximum number of Eth-Trunks:8 Maximum number of dynamic ARP entries in the system:256
Product Code	S2350-28TP-PWR-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S2350-28TP-PWR-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S2350-20TP-PWR-EI-AC	S2350-20TP-PWR-EI-AC(16 Ethernet 10/100 PoE+ ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC 110/220V)

S2350-28TP-EI-AC	S2350-28TP-EI-AC(24 Ethernet 10/100 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC 110/220V,front access)
------------------	---

Request availability: [Ask for current stock](#) of S2350-28TP-PWR-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).