

Huawei Quidway S2700 Switch S2700-18TP-EI-AC

Model: S2700-18TP-EI-AC | Brand: HUAWEI

Product Overview

S2700-18TP-EI-AC Mainframe(16 Ethernet 10/100 ports, 2 dual-purpose 10/100/1000 or SFP, AC 110/220V)

Product page: <https://www.linknewnet.com/products/s2700-18tp-ei-ac>

Quick Specifications

Attribute	Value
Downlink ports	24 × 10/100Base-TX Ethernet ports
Uplink ports	2 dual-purpose 10/100/1000 or SFP
Dimensions (W x D x H)	442 × 220 × 43.6 mm
Weight	S2700-18TP-EI<2.4 kg
Power consumption	S2700-18TP-EI<14.5 W
Reliability	STP (IEEE 802.1d), RSTP (IEEE 802.1w), MSTP (IEEE 802.1s), and RRPP topology and RRPP multi-instance
Surge protection	Surge protection capability of service ports: 6 kV (The surge protection capability of service ports on PoE switches is 1 kV.)
Operating environment	Long-term operating temperature: −5°C to + 50°C Relative humidity: 10% to 90% (non-condensing)
IPv6 feature	IPv6 protocol Static IPv6 routes Supports MLD v1/v2 snooping.
Power	AC: Rated voltage range: 100 V to 240 V AC, 50/60 Hz Maximum voltage: 90 to 264 V AC, 50/60 Hz
Product Code	S2700-18TP-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S2700-18TP-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S2700-18TP-SI-AC	S2700-18TP-SI-AC Mainframe(16 Ethernet 10/100 ports, 2 dual-purpose 10/100/1000 or SFP, AC 110/220V)
S2700-26TP-EI-AC	S2700-26TP-EI-AC Mainframe(24 Ethernet 10/100 ports, 2 dual-purpose 10/100/1000 or SFP, AC 110/220V)

Request availability: [Ask for current stock](#) of S2700-18TP-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).