

Huawei S2700 Series Switches S2720-28TP-EI-AC

Model: S2720-28TP-EI-AC | Brand: HUAWEI

Product Overview

Huawei S2720-28TP-EI-AC 24 port Ethernet port 10/100 ports Switch

Product page: <https://www.linknewnet.com/products/s2720-28tp-ei-ac>

Quick Specifications

Attribute	Value
Memory (RAM)	256 MB
Flash	200 MB
Mean time between failures (MTBF)	44.3 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±6 kV
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Dimensions (H x W x D)	43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.7 in.)
Weight (with packaging)	3 kg (6.62 lb)
Stack ports	Two uplink 1000BASE-X optical ports
RTC	Not supported
RPS	Not supported
PoE	Not supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Operating altitude	0-5000 m (0-16404 ft.)
Certification	EMC certification Safety certification Manufacturing certification
Part number	02359395
Product Code	S2720-28TP-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S2720-28TP-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S2720-28TP-PWR-EI-L	16 * Ethernet 10/100 Base-T ports, 8 * Ethernet 10/100/1000 Base-T ports, 2 * Gig SFP ports, 2 *combo Gig ports

S2720-12TP-EI	Huawei S2720-EI switch, 4 Ethernet 10/100 Base-Tx ports, 4 Ethernet 10/100/1000 Base-T ports, 2 Gig SFP ports, 2 combo Gig ports, AC 110/220V
---------------	---

Request availability: [Ask for current stock](#) of S2720-28TP-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).