

Huawei S2720 Series Switches S2720-28TP-PWR-EI-L

Model: S2720-28TP-PWR-EI-L | Brand: HUAWEI

Product Overview

16 * Ethernet 10/100 Base-T ports, 8 * Ethernet 10/100/1000 Base-T ports, 2 * Gig SFP ports, 2 *combo Gig ports

Product page: <https://www.linknewnet.com/products/s2720-28tp-pwr-ei-l>

Quick Specifications

Attribute	Value
Item	Description
PoE	Supported
Memory (RAM)	512 MB
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Stack ports	Two 1000BASE-X ports
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Certification	EMC certification Safety certification Manufacturing certification
Product Code	S2720-28TP-PWR-EI-L
Brand	HUAWEI

Replacement / Alternative Options

If the S2720-28TP-PWR-EI-L is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S2720-28TP-EI-AC	Huawei S2720-28TP-EI-AC 24 port Ethernet port 10/100 ports Switch
S2720-12TP-EI	Huawei S2720-EI switch, 4 Ethernet 10/100 Base-Tx ports, 4 Ethernet 10/100/1000 Base-T ports, 2 Gig SFP ports, 2 combo Gig ports, AC 110/220V

Request availability: [Ask for current stock](#) of S2720-28TP-PWR-EI-L or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).