

Huawei S2720-EI Enterprise Switches

S2720-52TP-PWR-EI

Model: S2720-52TP-PWR-EI | Brand: HUAWEI

Product Overview

Huawei S2720-EI switch, 32 Ethernet 10/100 Base-Tx ports, 16 Ethernet 10/100/1000 Base-T ports, 4 Gig SFP ports, 370W PoE

Product page: <https://www.linknewnet.com/products/s2720-52tp-pwr-ei>

Quick Specifications

Attribute	Value
Item	Description
Memory (RAM)	512 MB
Flash	512 MB in total.
Mean time between failures (MTBF)	38 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Power supply surge protection	±6 kV in differential mode, ± 6 kV in common mode
Stack ports	Four 1000BASE-X ports
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Operating altitude	0-5000 m (0-16404 ft.)
Product Code	S2720-52TP-PWR-EI
Brand	HUAWEI

Replacement / Alternative Options

If the S2720-52TP-PWR-EI is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S2720-28TP-EI-AC	Huawei S2720-28TP-EI-AC 24 port Ethernet port 10/100 ports Switch
S2720-28TP-PWR-EI-L	16 * Ethernet 10/100 Base-T ports, 8 * Ethernet 10/100/1000 Base-T ports, 2 * Gig SFP ports, 2 *combo Gig ports

Request availability: [Ask for current stock](#) of S2720-52TP-PWR-EI or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).