

Huawei S2700 Series Switch S2751-28TP-PWR-EI-AC

Model: S2751-28TP-PWR-EI-AC | Brand: HUAWEI

Product Overview

S2751-28TP-PWR-EI-AC(12 Ethernet 10/100 PoE+ ports,12 Ethernet 10/100 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC 110/220V)

Product page: <https://www.linknewnet.com/products/s2751-28tp-pwr-ei-ac>

Quick Specifications

Attribute	Value
Downlink ports	24 × 10/100Base-TX Ethernet ports
Uplink ports	2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP
IPv6 feature	IPv6 protocol Static IPv6 routes Supports MLD v1/v2 snooping.
Multicast	MVLAN Controllable multicast IGMP v1/v2/v3 snooping Port-based rate limiting for multicast packets
Traffic sampling	sFlow
Surge protection	Surge protection capability of service ports: 6 kV
Operating environment	Long-term operating temperature: −5°C to + 50°C Relative humidity: 10% to 90% (non-condensing)
Power	AC: Rated voltage range: 100 V to 240 V AC, 50/60 Hz Maximum voltage: 90 to 264 V AC, 50/60 Hz
Dimensions (W x D x H)	442 × 310 × 43.6 mm
Weight	S2751-28TP-PWR-EI-AC<4.5 kg
Power consumption	S2751-28TP-PWR-EI-AC<147 W (PoE < 124W)
Product Code	S2751-28TP-PWR-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S2751-28TP-PWR-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ET1BS12712E1	Huawei S12700E-12 assembly chassis
ET1BS12708E0	Huawei S12700E-8 assembly chassis

Request availability: [Ask for current stock](#) of S2751-28TP-PWR-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).