

H3C S5130S-28P-EI L2 Ethernet Switch with 24*10/100/1000BASE-T Ports and 4*1000BASE-X SFP Ports,(AC)

Model: S5130S-28P-EI | Brand: H3C

Product Overview

H3C S5130S-28P-EI L2 Ethernet Switch with 24*10/100/1000BASE-T Ports and 4*1000BASE-X SFP Ports,(AC)

Product page: <https://www.linknewnet.com/products/s5130s-28p-ei>

Quick Specifications

Attribute	Value
Port Switching capacity	56Gbps
Forwarding capacity	42Mpps
Box Switching capacity	336Gbps
CPU	1 Core, 800MHz
Flash/SDRAM	256MB/512MB
Latency (64byte/μs)	GE: < 5μs
Dimensions(W× D×H)	440×160×43.6 mm
Weight	≤2.5kg
10/100/1000 Base-T port	24
SFP Port	4
Maximum Stacking Bandwidth	16Gbps
Maximum stacking Num	9
Input Voltage	AC: Rated voltage range: 100V~240V AC, 50/60Hz
Power Consumption	MIN: AC:9W MAX: AC:23W
Fan NUM	Fanless
MTBF(Year)	150.86
MTTR(Hour)	1
Storage Temperature	-40■ ~ 70■
Product Code	S5130S-28P-EI
Brand	H3C

Replacement / Alternative Options

If the S5130S-28P-EI is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5130S-12TP-EI	H3C 8 Gigabit electrical ports 4 Gigabit optical ports Network management switch
S5130S-10P-EI-H1	H3C 8x10/100/1000BASE-T Ethernet ports, 2x1G SFP ports

Request availability: [Ask for current stock](#) of S5130S-28P-EI or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).