

Huawei S5300 Series Switch S5300-28P-LI-BAT

Model: S5300-28P-LI-BAT | Brand: HUAWEI

Product Overview

S5300-28P-LI-BAT(24 Ethernet 10/100/1000 ports,4 Gig SFP,1 slot with battery,AC 110/220V)

Product page: <https://www.linknewnet.com/products/s5300-28p-li-bat>

Quick Specifications

Attribute	Value
Memory (RAM)	256 MB
Flash	200 MB
Mean time between failures (MTBF)	57.9 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±6 kV
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Dimensions (W x D x H)	442.0 mm x 310.0 mm x 43.6 mm (17.4 in. x 12.2 in. x 1.72 in.)
Weight	≤ 5 kg (11.02 lb)
Stack ports	Not supported
RPS	Not supported
PoE	Not supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -36 V DC to -72 V DC
Relative humidity	5% to 95%, noncondensing
Operating altitude	DC power modules configured: 0-2000 m (0-6562 ft.) AC power modules or battery modules configured: 0-5000 m (0-16404 ft.)
Certification	EMC certification Safety certification Manufacturing certification
Product Code	S5300-28P-LI-BAT
Brand	HUAWEI

Replacement / Alternative Options

If the S5300-28P-LI-BAT is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5300-10P-LI-AC	S5300-10P-LI-AC Mainframe(8 GE RJ45,2 GE SFP,AC 110/220V)
S5300-28P-LI-24S-4AH	S5300-28P-LI-24S-4AH(28 Gig SFP,4 of which are dual-purpose 10/100/1000 or SFP,with 1 battery of 4AH,AC 110/220V)

Request availability: [Ask for current stock](#) of S5300-28P-LI-BAT or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).