

Huawei S5300 Series Switch S5320-32C-HI-24S-AC

Model: S5320-32C-HI-24S-AC | Brand: HUAWEI

Product Overview

S5320-32C-HI-24S-AC (24 Gig SFP,8 of which are dual-purpose 10/100/1000 or SFP,4 10 Gig SFP+, with 600W AC power supply)

Product page: <https://www.linknewnet.com/products/s5320-32c-hi-24s-ac>

Quick Specifications

Attribute	Value
Item	Description
Memory (RAM)	4 GB
Flash	400 MB
Mean time between failures (MTBF)	56.21 years when no interface card is configured, 52.63 years when a 4-port 10GE interface card is configured
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Dimensions (W x D x H)	442.0 mm x 420.0 mm x 44.4 mm (17.4 in. x 16.5 in. x 1.74 in.)
Weight	Empty: ≤ 6 kg (13.23 lb) Fully loaded: ≤ 10 kg (22.05 lb)
Stack ports	Four fixed 10GE SFP+ ports on the front panel or ports on the 4-port 10GE SFP+ rear interface card
RPS	Not supported
PoE	Not supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -38.4 V DC to -72 V DC
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Product Code	S5320-32C-HI-24S-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5320-32C-HI-24S-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5320-28X-SI	S5320-28X-SI (24 Ethernet 10/100/1000 ports,4 of which are dual-purpose 10/100/1000 or SFP,4 10 Gig SFP+)
S5320-28X-SI-DC	S5320-28X-SI-DC (24 Ethernet 10/100/1000 ports,4 of which are dual-purpose 10/100/1000 or SFP,4 10 Gig SFP+,with 150W DC power supply)

Request availability: [Ask for current stock](#) of S5320-32C-HI-24S-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).