

Huawei S5700 Series Switches S5700-28C-PWR-EI-AC

Model: S5700-28C-PWR-EI-AC | Brand: HUAWEI

Product Overview

S5700-28C-PWR-EI-AC(24 Ethernet 10/100/1000 PoE+ ports,with 1 interface slot,with 500W AC power supply)

Product page: <https://www.linknewnet.com/products/s5700-28c-pwr-ei-ac>

Quick Specifications

Attribute	Value
Switching Capacity	256 Gbit/s
Forwarding Performance	96 Mpps
Dimensions (W x D x H)	442 mm x 420 mm x 43.6 mm
Power Consumption	< 842W (PoE: 740W)
Fixed Ports	24 x 10/100/1,000 Base-T ports
Extended Slots	S5700C provides two extended slots, one for an uplink subcard and the other for a stack card.
IP Routing	Static routing, RIPv1/v2, RIGng, OSPF, OSPFv3, IS-IS, IS-ISv6, BGP, BGP4+, and ECMP
Operating Environment	Operating temperature: 0°C to 50°C Relative humidity: 5% to 95% (non-condensing)
Input Voltage	AC: Rated voltage range: 100V to 240V AC, 50 Hz/60 Hz Maximum voltage range: 90V to 264V AC, 50 Hz/60 Hz
Product Code	S5700-28C-PWR-EI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5700-28C-PWR-EI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5700-10P-LI-AC	24 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220V
S5700-10P-PWR-LI-AC	8 Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V

Request availability: [Ask for current stock](#) of S5700-28C-PWR-EI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).