

Huawei S5700 Series Switches S5700-28P-LI-AC

Model: S5700-28P-LI-AC | Brand: HUAWEI

Product Overview

24 Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V

Product page: <https://www.linknewnet.com/products/s5700-28p-li-ac>

Quick Specifications

Attribute	Value
Fixed Ports	S5700-28P-LI-AC/S5700-28P-PWR-LI/S5700-28P-LI-BAT: 24 x 10/100/1,000 Base-T Ethernet ports, 4 x GE SFP ports
Dimensions (W x D x H)	442 mm x 220 mm x 43.6 mm
Power Consumption	S5700-28P-LI-AC < 24W
Jumbo frame	10K
IP Routing	Static route, RIP, RIPng (S5700-10P-LI-AC/S5700-10P-PWR-LI-AC do not support RIPng)
Access Security	DHCP relay, DHCP server, DHCP snooping, and DHCP security
Lightning Protection	Service interface: 6 kV
Operating Environment	Long-term operating temperature: 0°C to 50°C Relative humidity: 5% to 95% (non-condensing)
Input Voltage	AC: Rated voltage range: 100V to 240V, 50 Hz/60 Hz, Maximum voltage range: 90V to 264V, 47 Hz/63 Hz
Power Socket Position	rear power sockets
Battery	One slot for lead-acid battery charger module (supported by battery LAN switches)
Product Code	S5700-28P-LI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5700-28P-LI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5700-10P-LI-AC	24 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220V
S5700-10P-PWR-LI-AC	8 Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V

Request availability: [Ask for current stock](#) of S5700-28P-LI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).