

Huawei S5700 Series Switches S5700-28X-LI-DC

Model: S5700-28X-LI-DC | Brand: HUAWEI

Product Overview

S5700-28X-LI-DC(24 Ethernet 10/100/1000 ports,4 10 Gig SFP+,DC -48V)

Product page: <https://www.linknewnet.com/products/s5700-28x-li-dc>

Quick Specifications

Attribute	Value
Switching Capacity	256 Gbit/s
Fixed Ports	24 x 10/100/1,000 Base-T Ethernet ports, 4 x 10 GE SFP+ ports
Jumbo frame	10K
Dimensions (W x D x H)	442 mm x 220 mm x 43.6 mm
Power Consumption	< 42W;
IP Routing	Static route, RIP, RIPng
Access Security	DHCP relay, DHCP server, DHCP snooping, and DHCP security
Lightning Protection	Service interface: 6 kV
Power Socket Position	rear power sockets
Battery	One slot for lead-acid battery charger module (supported by battery LAN switches)
Operating Environment	Long-term operating temperature: 0°C to 50°C Relative humidity: 5% to 95% (non-condensing)
Input Voltage	DC: Rated voltage range: -48V to -60V, Maximum voltage range: -36V to -72V Note: Models supporting PoE do not use DC power supplies.
Product Code	S5700-28X-LI-DC
Brand	HUAWEI

Replacement / Alternative Options

If the S5700-28X-LI-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5700-10P-LI-AC	24 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220V
S5700-10P-PWR-LI-AC	8 Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V

Request availability: [Ask for current stock](#) of S5700-28X-LI-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).