

Huawei S5700 Series Switches S5700-52X-LI-48CS-AC

Model: S5700-52X-LI-48CS-AC | Brand: HUAWEI

Product Overview

S5700-52X-LI-48CS-AC(48 Gig CSFP or 24 Gig SFP,4 of which are dual-purpose 10/100/1000 or CSFP,4 10 Gig SFP+,AC 110/220V,front access)

Product page: <https://www.linknewnet.com/products/s5700-52x-li-48cs-ac>

Quick Specifications

Attribute	Value
Fixed port	48x1000Base-X(CSFP) or 24 × 1000Base-X, 4 of which are dual-purpose 10/100/1000 or Base-X(CSFP), 4 × 10GE SFP+
IP routing	Static routing
Dimensions (W x D x H)	442 x 220 x 43.6 mm
Powerconsumption	<79.9W
Access Security	DHCP Relay, DHCP Server, DHCP Snooping, DHCP Security
Interoperability	Supports VBST (Compatible with PVST/PVST+/RPVST) Supports LNP (Similar to DTP) Supports VCMP (Similar to VTP)
Operating environment	Operating temperature: 0℃–50℃ Relative humidity: 10%–90% (non-condensing)
Input voltage	AC: Rated voltage range: 100 V to 240 V AC, 50/60 Hz Maximum voltage range: 90 V to 264 V AC, 47/63 Hz
Product Code	S5700-52X-LI-48CS-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5700-52X-LI-48CS-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5700-10P-LI-AC	24 Ethernet 10/100/1000 ports, 4 10 Gig SFP+, AC 110/220V
S5700-10P-PWR-LI-AC	8 Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V

Request availability: [Ask for current stock](#) of S5700-52X-LI-48CS-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).