

Huawei S5700 Series Switches S5701-28TP-PWR-LI-AC

Model: S5701-28TP-PWR-LI-AC | Brand: HUAWEI

Product Overview

S5701-28TP-PWR-LI-AC(12 Ethernet 10/100/1000 PoE+ ports,12 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC)

Product page: <https://www.linknewnet.com/products/s5701-28tp-pwr-li-ac>

Quick Specifications

Attribute	Value
Jumbo frame	10K
Power Socket Position	rear power sockets
IP Routing	Static route, RIP, RIPng (S5700-10P-LI-AC/S5700-10P-PWR-LI-AC do not support RIPng)
Access Security	DHCP relay, DHCP server, DHCP snooping, and DHCP security
Lightning Protection	Service interface: 6 kV
Dimensions (W x D x H)	S5701-28TP-PWR-LI-AC: 442 mm x 310 mm x 43.6 mm
Power Consumption	S5701-28TP-PWR-LI-AC < 238.7W (PoE: 185W)
Operating Environment	Long-term operating temperature: 0°C to 50°C Relative humidity: 5% to 95% (non-condensing)
Input Voltage	AC: Rated voltage range: 100V to 240V, 50 Hz/60 Hz, Maximum voltage range: 90V to 264V, 47 Hz/63 Hz
Battery	One slot for lead-acid battery charger module (supported by battery LAN switches)
Product Code	S5701-28TP-PWR-LI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5701-28TP-PWR-LI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5701-28X-LI-24S-AC	S5701-28X-LI-24S-AC(20 Gig SFP,4 dual-purpose 10/100/1000 and SFP,4 10 Gig SFP+,AC 110/220V)
S5701-28X-LI-AC	S5701-28X-LI-AC(24 Ethernet 10/100/1000 ports,4 10 Gig SFP+,AC 110/220V)

Request availability: [Ask for current stock](#) of S5701-28TP-PWR-LI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).