

Huawei S5700 Series Switches S5720-16X-PWH-LI-AC

Model: S5720-16X-PWH-LI-AC | Brand: HUAWEI

Product Overview

S5720-16X-PWH-LI-AC(12 Ethernet 10/100/1000 PoE++ ports,2 Ethernet 10/100/1000 ports,2 10 Gig SFP+,360W POE AC 110/220V)

Product page: <https://www.linknewnet.com/products/s5720-16x-pwh-li-ac>

Quick Specifications

Attribute	Value
Memory (RAM)	512 MB
Flash	240 MB
Mean time between failures (MTBF)	9.3 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Dimensions (W x D x H)	320.0 mm x 263.0 mm x 43.6 mm
Weight (including packaging materials)	4.7 kg (10.36 lb)
Stack ports	All electrical ports and optical ports
PoE	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Relative humidity	5% to 95%, noncondensing
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Product Code	S5720-16X-PWH-LI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5720-16X-PWH-LI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720-32X-EI-AC	Huawei S5700 Series Switch S5720-32X-EI-AC
S5720-12TP-LI-AC	S5720-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720-16X-PWH-LI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).