

Huawei S5700 Series Switches S5720-28X-LI-24S-DC

Model: S5720-28X-LI-24S-DC | Brand: HUAWEI

Product Overview

S5720-28X-LI-24S-DC(24 Gig SFP,8 of which are dual-purpose 10/100/1000 or SFP,4 10 Gig SFP+,DC -48V,front access)

Product page: <https://www.linknewnet.com/products/s5720-28x-li-24s-dc>

Quick Specifications

Attribute	Value
Memory (RAM)	512 MB
Flash	240 MB
Mean time between failures (MTBF)	41 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Dimensions (W x D x H)	442.0 mm x 220.0 mm x 43.6 mm
Weight (including packaging materials)	3.3 kg (7.28 lb)
RTC	Not supported
RPS	Supported
PoE	Not supported
Rated voltage range	-48 V DC to -60 V DC
Maximum voltage range	-36 V DC to -72 V DC
Power supply surge protection	±1 kV in differential mode, ±2 kV in common mode
Stack ports	GE SFP optical ports except combo ports and 10GE SFP+ optical ports
Product Code	S5720-28X-LI-24S-DC
Brand	HUAWEI

Replacement / Alternative Options

If the S5720-28X-LI-24S-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720-32X-EI-AC	Huawei S5700 Series Switch S5720-32X-EI-AC
S5720-12TP-LI-AC	S5720-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720-28X-LI-24S-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).