

Huawei S5700 Series Switches S5720-32X-EI-DC

Model: S5720-32X-EI-DC | Brand: HUAWEI

Product Overview

S5720-32X-EI-DC (24 Ethernet 10/100/1000 ports,4 Gig SFP,4 10 Gig SFP+,DC -48V,front access)

Product page: <https://www.linknewnet.com/products/s5720-32x-ei-dc>

Quick Specifications

Attribute	Value
Switching Capacity	598 Gbit/s
Forwarding Performance	102 Mpps
DRAM and Flash Memory	SDRAM: 2 GB Flash: 340 MB
MAC Address Table	64k
Front Power Input	Yes
Typical Power Consumption	40.9W
Dimensions (W x D x H)	442 mm x 220 mm x 43.6 mm
Fixed Ports	24 x 10/100/1,000 Base-T, 4 x 100/1,000 Base-X SFP, 4 x 10 Gig SFP+
Extended Slot	NA
DRAM and Flash	SDRAM: 2 GB Flash: 340 MB
Jumbo Frame	12K
IP Routing	Static routing, RIPv1/v2, RIPvng, OSPF, OSPFv3, IS-IS, IS-ISv6, BGP, BGP4+, ECMP, and policy-based routing
Port Aggregation	LACP Up to 128 trunk groups Up to 8 member interfaces in each trunk group
Surge Protection	Surge protection capability of service ports: 6 kV
Input Voltage	DC: Rated voltage range: -48V to -60V Maximum voltage range: -36V to -72V
Product Code	S5720-32X-EI-DC
Brand	HUAWEI

Replacement / Alternative Options

If the S5720-32X-EI-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720-32X-EI-AC	Huawei S5700 Series Switch S5720-32X-EI-AC
S5720-12TP-LI-AC	S5720-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720-32X-EI-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).