

Huawei S5700 Series Switches S5720-52P-LI-AC

Model: S5720-52P-LI-AC | Brand: HUAWEI

Product Overview

48 Ethernet 10/100/1000 ports, 4 Gig SFP, AC power support

Product page: <https://www.linknewnet.com/products/s5720-52p-li-ac>

Quick Specifications

Attribute	Value
Item	Description
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	41 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Power supply surge protection	±6 kV in differential mode, ±6 kV in common mode
Stack ports	Forty-eight 10/100/1000BASE-T ports and four 1000BASE-X ports
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Operating temperature	0°C to 45°C (32°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature	-5°C to +55°C (23°F to 131°F) at an altitude of 0-1800 m (0-5906 ft.)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Product Code	S5720-52P-LI-AC
Brand	HUAWEI

Replacement / Alternative Options

If the S5720-52P-LI-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720-32X-EI-AC	Huawei S5700 Series Switch S5720-32X-EI-AC
S5720-12TP-LI-AC	S5720-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720-52P-LI-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).