

Huawei S5700 Series Switches S5720-52X-LI-DC

Model: S5720-52X-LI-DC | Brand: HUAWEI

Product Overview

S5720-52X-LI-DC(48 Ethernet 10/100/1000 ports,4 10 Gig SFP+,DC -48V)

Product page: <https://www.linknewnet.com/products/s5720-52x-li-dc>

Quick Specifications

Attribute	Value
Memory (RAM)	512 MB
Flash	240 MB
Mean time between failures (MTBF)	41 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Dimensions (W x D x H)	442.0 mm x 220.0 mm x 43.6 mm
Weight (including packaging materials)	3.5 kg (7.72 lb)
RTC	Not supported
RPS	Supported
PoE	Not supported
Rated voltage range	-48 V DC to -60 V DC
Maximum voltage range	-36 V DC to -72 V DC
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Stack ports	Forty-eight 10/100/1000BASE-T ports and four 10G SFP+ ports
Product Code	S5720-52X-LI-DC
Brand	HUAWEI

Replacement / Alternative Options

If the S5720-52X-LI-DC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720-32X-EI-AC	Huawei S5700 Series Switch S5720-32X-EI-AC
S5720-12TP-LI-AC	S5720-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720-52X-LI-DC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).