

Huawei S5700 Series Switches

S5720S-28TP-PWR-LI-ACL

Model: S5720S-28TP-PWR-LI-ACL | Brand: HUAWEI

Product Overview

S5720S-28TP-PWR-LI-ACL(8 Ethernet 10/100/1000 PoE+,16 Ethernet 10/100/1000,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,124W POE AC,front access)

Product page: <https://www.linknewnet.com/products/s5720s-28tp-pwr-li-acl>

Quick Specifications

Attribute	Value
Memory (RAM)	512 MB
Flash	240 MB
Mean time between failures (MTBF)	42 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ± 7 kV
Dimensions (W x D x H)	442.0 mm x 220.0 mm x 43.6 mm
Weight (including packaging materials)	3.6 kg (7.94 lb)
PoE	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz
Relative humidity	5% to 95%, noncondensing
Power supply surge protection	± 6 kV in differential mode, ± 6 kV in common mode
Stack ports	Twenty-four 10/100/1000BASE-T ports and two 1000BASE-X ports
Product Code	S5720S-28TP-PWR-LI-ACL
Brand	HUAWEI

Replacement / Alternative Options

If the S5720S-28TP-PWR-LI-ACL is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5720S-12TP-LI-AC	S5720S-12TP-LI-AC(8 Ethernet 10/100/1000 ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP,AC 110/220V)
S5720S-12TP-PWR-LI-AC	S5720S-12TP-PWR-LI-AC(8 Ethernet 10/100/1000 PoE+ ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP)

Request availability: [Ask for current stock](#) of S5720S-28TP-PWR-LI-ACL or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).