

Huawei S5700 Series Switches S5730-68C-HI-48S

Model: S5730-68C-HI-48S | Brand: HUAWEI

Product Overview

S5730-68C-HI-48S (48 GE SFP ports, 4 x 10 GE SFP+ ports, 2 expansion slots)

Product page: <https://www.linknewnet.com/products/s5730-68c-hi-48s>

Quick Specifications

Attribute	Value
Fixed Ports	48 GE SFP ports, 4 x 10 GE SFP+ ports
Dimensions (W x D x H)	442 mm x 420 mm x 44.4 mm
Extended Slots	Two extended slots (one of them is reserved), supporting 8-port 10 GE electrical, 8-port 10 GE optical, or 2-port 40 GE optical interface card
Input Voltage	AC: Rated AC voltage: 100V to 240V; 50/60 Hz Max. AC voltage: 90V to 264V; 47 Hz to 63 Hz
Power Consumption	100W
Operating Temperature	0m to 1,800m altitude: 0°C to 45°C 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.
Relative Humidity	5% to 95% (non-condensing)
Heat Dissipation	Air cooling heat dissipation and intelligent speed adjustment
MAC Address Table	IEEE 802.1d standards compliance
VLAN	4094 VLANs
Wireless Service	AP access control, AP domain management, and AP configuration template management
Ethernet Loop Protection	RRPP ring topology and RRPP multi-instance
MPLS	MPLS L3VPN
IP Routing	Static routes, RIP v1/2, RIPng, OSPF, OSPFv3, IS-IS, IS-ISv6, BGP, BGP4+, ECMP, and routing policy
Interoperability	VLAN-Based Spanning Tree (VBST), working with PVST, PVST+, and RPVST
IPv6 Features	Neighbor Discover (ND)
Multicast	IGMP v1/v2/v3 snooping and IGMP fast leave
QoS/ACL	Rate limitation in the inbound and outbound directions of a port
Security	Hierarchical user management and password protection
Reliability	LACP
Product Code	S5730-68C-HI-48S
Brand	HUAWEI

Replacement / Alternative Options

If the S5730-68C-HI-48S is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5730-36C-HI	S5730-36C-HI (24 x 10/100/1,000 BASE-T ports, 4 x 10 GE SFP+ ports, 1 expansion slot, without power module)
S5730-36C-HI-24S	S5730-36C-HI-24S (24 GE SFP ports, 8 of which are dual-purpose 10/100/1,000 Base-T or SFP ports, 4 x 10 GE SFP+ ports, 1 expansion slot, without power

Request availability: [Ask for current stock](#) of S5730-68C-HI-48S or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).