

Huawei S5700 Series Switches S5730S-48C-PWR-EI

Model: S5730S-48C-PWR-EI | Brand: HUAWEI

Product Overview

Huawei S5730-EI switch, 24 x Ethernet 10/100/1,000 ports,PoE, 8 x 10 Gig SFP+

Product page: <https://www.linknewnet.com/products/s5730s-48c-pwr-ei>

Quick Specifications

Attribute	Value
Item	Description
Memory (RAM)	1 GB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	46.8 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Stack ports	Any 10GE SFP+ or 40GE QSFP+ ports Ports on the 2-port QSFP+ rear stack card
RTC	Supported
RPS	Not supported
PoE	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -38.4 V DC to -72 V DC
Product Code	S5730S-48C-PWR-EI
Brand	HUAWEI

Replacement / Alternative Options

If the S5730S-48C-PWR-EI is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5730S-48C-EI-AC	Huawei S5730-EI switch, 24 x Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+, with AC power supply
S5730S-68C-EI-AC	Huawei S5730-EI switch, 48 x Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+, with AC power supply

Request availability: [Ask for current stock](#) of S5730S-48C-PWR-EI or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).