

Huawei S5700 Series Switches S5735S-L48P4X-A1

Model: S5735S-L48P4X-A1 | Brand: HUAWEI

Product Overview

48x 10/100/1000BASE-T Ethernet ports, 4x 10 Gigabit SFP+, PoE+, AC power.

Product page: <https://www.linknewnet.com/products/s5735s-l48p4x-a1>

Quick Specifications

Attribute	Value
Typical power consumption [W]	58.7 W
Typical heat dissipation [BTU/hour]	200.29 BTU/hour
Maximum power consumption [W]	· Not providing the PoE function: 76.1 W 100% PoE loads: 456.1 W (PoE: 380 W)
Maximum heat dissipation [BTU/hour]	· Not providing the PoE function: 259.66 100% PoE loads: 1556.26
MTBF [year]	44.03 year
Number of card slots	0
Number of power slots	0
Number of fans modules	2
Redundant power supply	Not supported
Power supply mode	AC built-in
Rated input voltage [V]	· AC input: 100 V AC to 240 V AC, 50/60 Hz High-Voltage DC input: 240 V DC
Input voltage range [V]	· AC input: 90 V AC to 290 V AC, 45 Hz to 65 Hz High-Voltage DC input: 190 V DC to 290 V DC
Maximum input current [A]	6 A
Memory	512 MB
Flash memory	512 MB
Console port	RJ45
USB	Supported
RTC	Not supported
RPS input	Not supported
Service port surge protection [kV]	Common mode: ±7 kV
Product Code	S5735S-L48P4X-A1
Brand	HUAWEI

Replacement / Alternative Options

If the S5735S-L48P4X-A1 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5735S-H24S4X-A	S5735S-H24S4X combination configuration (24 Gigabit SFP, 4 10G SFP +, including 1 AC power)
S5735S-H24S4X-MA	S5735S-H24S4X-M combined configuration (24 Gigabit SFP, 4 10G SFP +, including 1 AC power)

Request availability: [Ask for current stock](#) of S5735S-L48P4X-A1 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).