

Huawei S5700 Series Switches S5735S-S32ST4X-A

Model: S5735S-S32ST4X-A | Brand: HUAWEI

Product Overview

Huawei S5735-S switch, 24 GE SFP Ports, 8 10/100/1000BASE-T, 4 10G SFP+, 1 60W AC Power Supply

Product page: <https://www.linknewnet.com/products/s5735s-s32st4x-a>

Quick Specifications

Attribute	Value
Memory (RAM)	1 GB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	68.59 years
Mean time to repair (MTTR)	1.75 hours
Availability	> 0.99999
Service port surge protection	Common mode: ±7 kV
Power supply surge protection	Using AC power modules: ±6 kV in differential mode, ±6 kV in common mode Using DC power modules: ±2 kV in differential mode, ±4 kV in common mode
Stack ports	Any 10/100/1000BASE-T ports, 100/1000BASE-X ports, or 10GE SFP+ ports (applicable in V200R019C10 and later versions)
Rated voltage range	AC input: 100 V AC to 240 V AC, 50/60 Hz High-Voltage DC input: 240 V DC DC input: -48 V DC to -60 V DC
Maximum voltage range	AC input: 90 V AC to 264 V AC, 47 Hz to 63 Hz High-Voltage DC input: 190 V DC to 290 V DC DC input: -38.4 V DC to -72 V DC
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	5% to 95%, noncondensing
Product Code	S5735S-S32ST4X-A
Brand	HUAWEI

Replacement / Alternative Options

If the S5735S-S32ST4X-A is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
S5735S-H24S4X-A	S5735S-H24S4X combination configuration (24 Gigabit SFP, 4 10G SFP +, including 1 AC power)
S5735S-H24S4X-MA	S5735S-H24S4X-M combined configuration (24 Gigabit SFP, 4 10G SFP +, including 1 AC power)

Request availability: [Ask for current stock](#) of S5735S-S32ST4X-A or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).