

SM-40 - Cisco Firepower 9000 Series Appliances

Model: SM-40 | Brand: CISCO

Product Overview

FirePower 9000

Product page: <https://www.linknewnet.com/products/sm-40>

Quick Specifications

Attribute	Value
Brand	Cisco
Product Name	FirePower 9000
Firewall Throughput	Up to 320 Gbps
Threat Prevention Throughput	Up to 60 Gbps
NGFW Throughput	Up to 50 Gbps
Concurrent Sessions	Up to 200 million
New Connections per Second	Up to 2 million
Maximum VPN Peers	Up to 10,000
Security Contexts	Up to 250
Interfaces	10/100/1000, 10GbE, 40GbE
High Availability	Active/Active, Active/Standby
Redundancy	Hot Swappable Components
Management	Centralized Management with Cisco Firepower Management Center
Form Factor	2 RU
Power Supply	AC/DC Options, Redundant Power Supplies
Chassis	Modular
Operating Temp	32°F to 104°F (0°C to 40°C)
Storage Temp	-4°F to 149°F (-20°C to 65°C)
Humidity	10% to 90% RH
Compliance	FIPS, Common Criteria, ICSA Firewall, and IPsec
Product Code	SM-40
Brand	CISCO

Replacement / Alternative Options

If the SM-40 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of SM-40 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).