

SM-56 - Cisco Firepower 9000 Series Appliances

Model: SM-56 | Brand: CISCO

Product Overview

FirePower 9000

Product page: <https://www.linknewnet.com/products/sm-56>

Quick Specifications

Attribute	Value
Brand	Cisco
Product Name	FirePower 9000
Model	SM-56
Firewall Throughput	12 Gbps
Maximum Concurrent Sessions	1 Million
Maximum VLANs	6000
Maximum IPSec VPN Peers	10,000
Next-Gen IPS Throughput	10 Gbps
Power Supply	AC or DC
Network Interface Ports	48 x 1/10 Gbps SFP+, 2 x 40 Gbps QSFP+
Redundancy	Failover
Form Factor	2U Rack-mountable
Cooling	Front to Back Airflow
Management	CLI, Web Interface
Operating Environment	0 to 45°C (32 to 113°F)
Storage Environment	-20 to 70°C (-4 to 158°F)
Relative Humidity	10% to 90%, non-condensing
Compliance	FCC, CE, UL
Chassis Dimensions	17.24 in x 3.47 in x 20.26 in
Memory	16 GB
Product Code	SM-56
Brand	CISCO

Replacement / Alternative Options

If the SM-56 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC
-----------	---

Request availability: [Ask for current stock](#) of SM-56 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).