

SM-X-1T3/E3= - Cisco ISR4000 Service Module

Model: SM-X-1T3/E3= | Brand: CISCO

Product Overview

One port T3/E3 Service module

Product page: <https://www.linknewnet.com/products/sm-x-1t3-e3>

Quick Specifications

Attribute	Value
Product Type	Service Module
Port	1 x T3/E3
Data Rate	44.736 Mbps (T3), 34.368 Mbps (E3)
Network Protocols	SONET/SDH, PPP, HDLC
Interface	BNC Coaxial Connectors
Form Factor	Plug-in module
Compatible Platforms	Cisco 4000 Series Integrated Services Routers
Redundancy	Supports Multi-Link PPP (MLPPP)
Mounting	Internal
Temperature Range	Operating: 32 to 104°F (0 to 40°C)
Storage Temperature	-40 to 158°F (-40 to 70°C)
Power Consumption	5.5W maximum
Humidity Range	10 to 85% non-condensing
LED Indicators	Link, Activity
EMC Certifications	GR-1089, EN55022, EN55024
Safety Certifications	UL 60950, CSA 22.2 No. 60950
Dimensions	5.3 x 1.1 x 7.1 inches (L x W x H)
Mean Time Between Failure (MTBF)	250,000 hours
Warranty	Limited Lifetime Warranty
Product Code	SM-X-1T3/E3=
Brand	CISCO

Replacement / Alternative Options

If the SM-X-1T3/E3= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
SM-X-16FXS/2FXO	16-port FXS and 2-port FXO single-wide service module
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of SM-X-1T3/E3= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).