

SM-X-24FXS/4FXO - Cisco 4000 Series ISRs Service Module

Model: SM-X-24FXS/4FXO | Brand: CISCO

Product Overview

24-port FXS and 4-port FXO single-wide service module

Product page: <https://www.linknewnet.com/products/sm-x-24fxs-4fxo>

Quick Specifications

Attribute	Value
Model	SM-X-24FXS/4FXO
Type	Service Module
Ports	24 FXS, 4 FXO
Form Factor	Single-Wide
Compatibility	Cisco ISR 4000 Series
Data Rates	Up to 1 Mbps (per port)
Connectors	RJ-11
Power Consumption	15W (typical)
Humidity	5% to 95% non-condensing
Ring Cadence	Configurable
Channel Density	Up to 28 ports
Compliance	RoHS, CE, FCC
Dimensions (W x D x H)	8.5 in x 7.25 in x 1.5 in
MTBF	300,000 hours
Voice Protocol Support	SIP, H.323
Codec Support	G.711, G.729
Firmware Upgradeable	Yes
Product Code	SM-X-24FXS/4FXO
Brand	CISCO

Replacement / Alternative Options

If the SM-X-24FXS/4FXO is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of SM-X-24FXS/4FXO or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).