

SPA-1CHOC3-CE-ATM - Cisco Catalyst 7600 Series Port Adapter

Model: SPA-1CHOC3-CE-ATM | Brand: CISCO

Product Overview

Cisco 7600 Shared Port Adapter 1 Port Channelized OC3/STM-1 ATM and Circuit Emulation SPA

Product page: <https://www.linknewnet.com/products/spa-1choc3-ce-atm>

Quick Specifications

Attribute	Value
Number of Ports	1
Model	SPA-1CHOC3-CE-ATM
Port Type	Channelized OC3/STM-1
Interface	ATM and Circuit Emulation
Form Factor	Shared Port Adapter
Compatibility	Cisco 7600 Series
Optical Interface	OC-3/STM-1
Supported Protocols	ATM, Circuit Emulation
Hot Swappable	Yes
Data Transfer Rate	155 Mbps
Cabling Type	Fiber
Power Consumption	Up to 10 Watts
Temperature Range	0°C to 40°C (Operation), -40°C to 70°C (Storage)
Humidity Range	10% to 90% non-condensing (Operation), 5% to 95% non-condensing (Storage)
Mean Time Between Failures (MTBF)	Over 200,000 hours
Connector Type	SC
Diagnostic LEDs	Link, Activity, Status
Compliance	RoHS, CE
Product Code	SPA-1CHOC3-CE-ATM
Brand	CISCO

Replacement / Alternative Options

If the SPA-1CHOC3-CE-ATM is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of SPA-1CHOC3-CE-ATM or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).