

SPA-1XOC12-POS= - Cisco Catalyst 7600 Series Port Adapter

Model: SPA-1XOC12-POS= | Brand: CISCO

Product Overview

Cisco 7600 1-port OC12/STM4 POS Shared Port Adapters

Product page: <https://www.linknewnet.com/products/spa-1xoc12-pos>

Quick Specifications

Attribute	Value
Model	SPA-1XOC12-POS=
Port Type	1-port OC12/STM4 POS
Compatibility	Cisco 7600 Series Routers
Data Rate	622 Mbps
Interface	POS (Packet over SONET/SDH)
Slot Requirement	Shared Port Adapter slot
Protocol	ATM, PPP, Cisco HDLC
Maximum Power Consumption	15W
Operating Temperature Range	0°C to 40°C
Storage Temperature Range	-40°C to 70°C
Relative Humidity	5% to 95% (non-condensing)
Dimensions (H x W x D)	1.56 x 6.75 x 8.00 inches
Optical WaveLength	1310 nm (TX), 1550 nm (RX)
Connectors	SC-type
Data Transfer Mode	Full Duplex
Chassis Compatibility	Cisco 7600-S and Cisco 7603
MTBF	200,000 hours
User Interface	Command Line Interface (CLI)
Product Code	SPA-1XOC12-POS=
Brand	CISCO

Replacement / Alternative Options

If the SPA-1XOC12-POS= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
SPA-1X10GE-L-V2	Cisco 7600 Series ModulesSPA-1X10GE-L-V2
SPA-1X10GE-WL-V2	Cisco 7600 Series ModulesSPA-1X10GE-WL-V2

Request availability: [Ask for current stock](#) of SPA-1XOC12-POS= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).