

SPA-2XCT3/DS0= - Cisco Catalyst 7600 Series Port Adapter

Model: SPA-2XCT3/DS0= | Brand: CISCO

Product Overview

Cisco 7600 2-port Channelized T3 to DS0 Shared Port Adapter

Product page: <https://www.linknewnet.com/products/spa-2xct3-ds0>

Quick Specifications

Attribute	Value
Compatibility	Cisco 7600 Series Routers
Interface	2-Port Channelized T3 to DS0
Port Configuration	2 Ports
Channelization	Channelized T3 to DS0
Supported Protocols	ATM, Frame Relay, HDLC, PPP
Maximum DS0 Channels	1344
Maximum T3 Ports	2
Form Factor	Plug-in Card
MTU (Maximum Transmission Unit)	4470 bytes
Power Consumption	40W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 65°C (-4°F to 149°F)
Humidity	10% to 90% non-condensing
Dimensions (W x D x H)	1.57 in x 7.28 in x 14.5 in
Hot-Swappable	Yes
Regulatory Compliance	CE, FCC, UL, IEEE
MTBF (Mean Time Between Failures)	200,000 hours
Product Type	Shared Port Adapter
LED Indicators	Link, Activity
Product Code	SPA-2XCT3/DS0=
Brand	CISCO

Replacement / Alternative Options

If the SPA-2XCT3/DS0= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
SPA-2X1GE	Cisco 2-port Gigabit Ethernet Shared Port Adapter
SPA-2X1GE-V2	Cisco 7600 Cisco 2-Port Gigabit Ethernet Shared Port Adapter

Request availability: [Ask for current stock](#) of SPA-2XCT3/DS0= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).