

SPA-IPSEC-2G= - Cisco Catalyst 7600 Series Port Adapter

Model: SPA-IPSEC-2G= | Brand: CISCO

Product Overview

Cisco 7600 / Catalyst 6500 IPSec VPN SPA - DES/3DES/AES

Product page: <https://www.linknewnet.com/products/spa-ipsec-2g>

Quick Specifications

Attribute	Value
Product Name	SPA-IPSEC-2G= (USED)
Associated Models	Cisco 7600 / Catalyst 6500
Functionality	IPSec VPN
Encryption Standards	DES/3DES/AES
Form Factor	Pluggable Module
Maximum Throughput	2 Gbps
Compatibility	Cisco 7600 Series Routers, Catalyst 6500 Series Switches
Layer	Layer 3
Protocol Support	IPSec
Redundancy Options	Supported with Dual Modules
QoS Support	Yes
Power Requirement	From Chassis
Operating Temperature	-5°C to 45°C (23°F to 113°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	5% to 95% non-condensing
MTBF	350,000 hours
Regulatory Compliance	FCC, CE, RoHS
Dimensions	20.3 x 17.3 x 1.6 cm
Product Code	SPA-IPSEC-2G=
Brand	CISCO

Replacement / Alternative Options

If the SPA-IPSEC-2G= is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
SPA-IPSEC-2G	Cisco 7600 / Catalyst 6500 IPSec VPN SPA - DES/3DES/AES
SPA-IPSEC-SSC400-1	Cisco 6500/7600 IPSec VPN SPA Bundle 1 (system only)

Request availability: [Ask for current stock](#) of SPA-IPSEC-2G= or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).