

Juniper SRX1600-SYS-JB-AC

Model: SRX1600-SYS-JB-AC | Brand: Juniper

Product Overview

SRX1600

Product page: <https://www.linknewnet.com/products/srx1600-sys-jb-ac>

Quick Specifications

Attribute	Value
Specifications	SRX1600
Onboard ports	16 x 1 GbE 10/100/1000 BASE-T
Out-of-Band (OOB) management ports	1 x 1 GbE G (RJ-45)
Dedicated high availability (HA) ports	2 x 1 GbE SFP
Console	1 (RJ-45)
USB 3.0 ports (Type A)	1
Storage (SSD)	1 x 120 GB
Form factor	1U
Size (W x H x D)	17.28 x 1.74 x 18.20 in (43.89 x 4.42 x 46.23 cm)
Redundant PSU	1+1
Maximum current consumption	2 A (for 110 V AC PSM) 1 A (for 230 V AC PSM) 4.7 A (for -40 V DC PSM)
Maximum inrush current	50 A for 1 cycle of AC (AC PSM) 40 A-pk (DC PSM)
Acoustic noise level	58 dB
Airflow/cooling	Front to back
Operating temperature	32° to 104° F (0° to 40° C at 6000 ft altitude)
Operating humidity	5% to 90% non-condensing
Meantime between failures (MTBF)	Over 100,000 hours (12 years)
FCC classification	Class A
RoHS compliance	RoHS 6
Firewall throughput 2 (IMIX)	12 Gbps
Product Code	SRX1600-SYS-JB-AC
Brand	Juniper

Replacement / Alternative Options

If the SRX1600-SYS-JB-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
EX4300-48P	Juniper EX4300 Series Ethernet Switch EX4300-48P48-port 10/100/1000 BaseT PoE-plus

EX4500-40F-VC1-BF	Juniper EX4500 Series Switch Chassis EX4500-40F-VC1-BF40-port 1/10G SFP+ Converged switch
-------------------	---

Request availability: [Ask for current stock](#) of SRX1600-SYS-JB-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).