

SRX240H2 - Juniper SRX Series Service Gateways

Model: SRX240H2 | Brand: Juniper

Product Overview

Juniper Networks SRX240 Services Gateway with 16 x GE ports, 4 x mini-PIM slots, and high memory (2GB RAM, 2GB FLASH)

Product page: <https://www.linknewnet.com/products/srx240h2>

Quick Specifications

Attribute	Value
Cabling technology	10/100/1000Base-T(X)
Data transfer rate	1.5 Gbit/s
Networking standards	IEEE 803.3at, IEEE 802.3af
Security features	4096 policies (max)
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Flash memory	2048 MB
Internal memory	2048 MB
Ethernet LAN (RJ-45) ports	16
Interface	Gigabit Ethernet
Heat dissipation	413 BTU/h
Power consumption (typical)	179 W
Power over Ethernet (PoE)	Yes
Power requirements	100-240, 150W
Supported network protocols	POP3, HTTP, SMTP, IMAP, FTP
Authentication method	RADIUS, RSA SecureID, LDAP
Firewall security	Yes
Compatible operating systems	JUNOS 10.3
Dimensions (WxDxH)	444 x 385 x 44 mm
Product Code	SRX240H2
Brand	Juniper

Replacement / Alternative Options

If the SRX240H2 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
SRX240-RMK	SRX240 Rack mount kit for 19" rack. Holds one unit.

SRX240H-POE-TAA	SRX services gateway 240 with 16 x GE ports, 4xmini-PIM slots, and high memory (1GB RAM, 1GB FLASH), w/ 16 ports POE (150W). TAA. Integrated power sup
-----------------	--

Request availability: [Ask for current stock](#) of SRX240H2 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).