

VWIC2-2MFT-T1/E1 - Cisco Voice/Wan Interface Cards

Model: VWIC2-2MFT-T1/E1 | Brand: CISCO

Product Overview

2-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1

Product page: <https://www.linknewnet.com/products/vwic2-2mft-t1-e1>

Quick Specifications

Attribute	Value
Product Type	Voice/WAN Interface Card
Model Number	VWIC2-2MFT-T1/E1
Ports	2
Generation	2nd
Supported Interfaces	T1/E1
Connectivity Technology	Wired
Form Factor	Plug-in Card
Device Supported	Router
Data Transfer Rate	Up to 2.048 Mbps
Voice Support	Yes
Network Standards	ITU-T G.703, G.704
Jitter Attenuation	Yes
Frequency Band	T1: 1.544 Mbps, E1: 2.048 Mbps
Connectors	2 x RJ-48C
Protocols	Frame Relay, PPP, HDLC
Echo Cancellation	Yes
Max Power Consumption	5.9W
Regulatory Compliance	FCC, CE, UL
Product Code	VWIC2-2MFT-T1/E1
Brand	CISCO

Replacement / Alternative Options

If the VWIC2-2MFT-T1/E1 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
VWIC2-1MFT-G703	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - G.703
VWIC2-1MFT-T1/E1	1-Port 2nd Gen Multiflex Trunk Voice/WAN Int. Card - T1/E1

Request availability: [Ask for current stock](#) of VWIC2-2MFT-T1/E1 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).