

WS-C2960L-24TS-LL - Cisco Catalyst 2960-L Series Switch

Model: WS-C2960L-24TS-LL | Brand: CISCO

Product Overview

Catalyst 2960L 24 port GigE, 4 x 1G SFP

Product page: <https://www.linknewnet.com/products/ws-c2960l-24ts-ll>

Quick Specifications

Attribute	Value
10/100/1000 Ethernet Ports	24
Uplink Interfaces	4 SFP
Available PoE Power	-
Fanless	Y
Dimensions (H x D x W)	1.73 x 9.45 x 17.5 in. (4.4 x 24 x 44.5 cm)
Net Weight	6.61 lb (3.0 kg)
RJ45 Ethernet	1
USB mini-B	1
CPU	ARMv7 800 MHz
DRAM	512 MB
Flash memory	256 MB
Forwarding bandwidth	28 Gbps
Switching bandwidth	56 Gbps
Jumbo Ethernet frame	10,240 bytes
MTBF in hours (Data)	2,412,947
MTBF in hours (PoE)	909,838
Forwarding rate (64-byte L3 packets)	41.67 Mpps
Maximum STP instances	64
Unicast MAC addresses	8K
Maximum active VLANs	64
Product Code	WS-C2960L-24TS-LL
Brand	CISCO

Replacement / Alternative Options

If the WS-C2960L-24TS-LL is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-C2918-24TT-C	24 10/100Mbps Ethernet port■2 10/100/1000Mbps uplink port
WS-C2918-24TC-C	24 10/100 Mbps Ethernet ports and 2 dual purpose uplink ports

Request availability: [Ask for current stock](#) of WS-C2960L-24TS-LL or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).