

WS-C3560CX-12PC-S Catalyst Compact switch

Model: WS-C3560CX-12PC-S | Brand: CISCO

Product Overview

Cisco Catalyst 3560-CX 12-port compact Switch Layer 3, POE- 12 x 10/100/1000 Ethernet Ports, 2 SFP&2GE uplinks- Data IP Base

Product page: <https://www.linknewnet.com/products/ws-c3560cx-12pc-s>

Quick Specifications

Attribute	Value
Forwarding Bandwidth	46 Gbps (with C3560CX-8XPD-S) 34 Gbps (with C3560CX-12PD-S) 16 Gbps (with 1 G uplinks)
Flash memory	128 MB
Memory DRAM	512 MB
Max VLANs	1023
VLAN IDs	4000
Maximum Transmission Unit (MTU)	Up to 9000 bytes
Jumbo frames	9198 bytes
Forwarding rate 64 Byte Packet	23.8 mpps
Indicators	Per-port status: Link integrity, disabled, activity, speed, full-duplex System status: System, link status, link duplex, link speed
Dimensions (H x W x D)	1.75 x 10.6 x 9.4 Inches
Weight	5.1 Pounds
Operating altitude	Up to 3048 m (Up to 10,000 ft)
Storage altitude	Up to 4000 m (Up to 15,000 ft)
Operating relative humidity	5% to 95% noncondensing
Storage relative humidity	5% to 95% noncondensing
Mean Time Between Failure (MTBF)	553,140
Safety standards	● UL 60950-1 ● CAN/CSA 22.2 No. 60950-1 ● EN 60950-1 ● IEC 60950-1 ● CE Marking ● GB 4943 ● IEC 60825
Environmental	Reduction of Hazardous Substances (ROHS) 6
Telco	Common Language Equipment Identifier (CLEI) code
Product Code	WS-C3560CX-12PC-S
Brand	CISCO

Replacement / Alternative Options

If the WS-C3560CX-12PC-S is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
-------	---------------

WS-C3560-24TS-E	CiscoCatalyst 3560 24 10/100 + 2 SFP Enhanced Image
WS-C3550-24-DC-SMI	Cisco Catalyst 3550 Series Switch WS-C3550-24-DC-SMI 24-10/100+2GBIC ports

Request availability: [Ask for current stock](#) of WS-C3560CX-12PC-S or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).